



# High Temperature Sockets for Pluggable Terminal Blocks

	20.155MH-HT	21.155MH-HT	20.155MHF-HT	21.155MHF-HT	20.155MV-HT	21.155MV-HT	20.155MVF-HT	21.155MVF-HT	
Pitch	Höhe	Pas	Passo	3.50mm (3.81mm)		3.50mm (3.81mm)		3.50mm (3.81mm)	
<b>Technical data</b>	<b>Technische Daten</b>	<b>Documentation technique</b>	<b>Dati tecnici</b>	<b>UL</b>	<b>IEC</b>	<b>UL</b>	<b>IEC</b>	<b>UL</b>	<b>IEC</b>
Rated voltage	Nennspannung	Tension assignée	Tensione nominale	300V	130V	300V	130V	300V	130V
Rated current	Nennstrom	Courant assigné	Corrente nominale	8A	8A	8A	8A	8A	8A
Wire range	Drahtbereich	Gamme des fils	Tipi di cavo						
Solid wire (AWG)	Massivdraht (AWG)	Fil rigide (AWG)	Cavo rigido (AWG)						
Stranded wire (AWG)	Normaldraht (AWG)	Fil standard (AWG)	Cavo standard (AWG)						
Rated surge voltage (UL/IEC(max))	Bemessungsstossspannung (max)	Surintention nominale (max)	Sovratensione nominale (max)	1.6/1.25/3kV		1.6/1.25/3kV		1.6/1.25/3kV	
Torque (Nm)	Drehmoment	Couple	Coppia						
Screw	Schraube	Vis	Vite						
Wire Strip length	Drahtabisolierlänge	Longueur isolée du fil	Lunghezza spellaggio cavo						
Temperature Range	Temperaturbereich	Plage de température	Gamma di temperature	-40°C +260°C		-40°C +260°C		-40°C +260°C	
<b>Part no.</b>	<b>Artikelbez</b>	<b>Numéro d'identification</b>	<b>Part. No.</b>	20.155MH/2HT (21.155MH/2HT)	20.155MH/24HT (21.155MH/24HT)	20.155MHF/2HT (21.155MHF/2HT)	20.155MHF/24HT (21.155MHF/24HT)	20.155MV/2HT (21.155MV/2HT)	20.155MV/24HT (21.155MV/24HT)
Pole	Pol	Pole	Polo						

	20.95MH-HT	21.95MH-HT	20.90MH-HT	21.90MH-HT	20.95MHFHT	21.95MHFHT	20.95MV-HT	21.95MV-HT	20.90MV-HT	21.90MV-HT	20.95MVFHT	21.95MVFHT	
Pitch	Höhe	Pas	Passo	5.00mm (5.08mm)		5.00mm (5.08mm)		5.00mm (5.08mm)		5.00mm (5.08mm)		5.00mm (5.08mm)	
<b>Technical data</b>	<b>Technische Daten</b>	<b>Documentation technique</b>	<b>Dati tecnici</b>	<b>UL</b>	<b>IEC</b>	<b>UL</b>	<b>IEC</b>	<b>UL</b>	<b>IEC</b>	<b>UL</b>	<b>IEC</b>	<b>UL</b>	<b>IEC</b>
Rated voltage	Nennspannung	Tension assignée	Tensione nominale	300V	250V	300V	250V	300V	250V	300V	250V	300V	250V
Rated current	Nennstrom	Courant assigné	Corrente nominale	15A	17.5A	15A	17.5A	15A	17.5A	15A	17.5A	15A	17.5A
Wire range	Drahtbereich	Gamme des fils	Tipi di cavo										
Solid wire (AWG)	Massivdraht (AWG)	Fil rigide (AWG)	Cavo rigido (AWG)										
Stranded wire (AWG)	Normaldraht (AWG)	Fil standard (AWG)	Cavo standard (AWG)										
Rated surge voltage (UL/IEC(max))	Bemessungsstossspannung (max)	Surintention nominale (max)	Sovratensione nominale (max)	1.6/2/4kV		1.6/2/4kV		1.6/2/4kV		1.6/2/4kV		1.6/2/4kV	
Torque (Nm)	Drehmoment	Couple	Coppia										
Screw	Schraube	Vis	Vite										
Wire Strip length	Drahtabisolierlänge	Longueur isolée du fil	Lunghezza spellaggio cavo										
Temperature Range	Temperaturbereich	Plage de température	Gamma di temperature	-40°C +260°C		-40°C +260°C		-40°C +260°C		-40°C +260°C		-40°C +260°C	
<b>Part no.</b>	<b>Artikelbez</b>	<b>Numéro d'identification</b>	<b>Part. No.</b>	20.95MH/2HT (21.95MH/2HT)	20.95MH/24HT (21.95MH/24HT)	20.90MH/2HT (21.90MH/2HT)	20.90MH/24HT (21.90MH/24HT)	20.95MHF/2HT (21.95MHF/2HT)	20.95MHF/24HT (21.95MHF/24HT)	20.95MV/2HT (21.95MV/2HT)	20.95MV/24HT (21.95MV/24HT)	20.90MV/2HT (21.90MV/2HT)	20.90MV/24HT (21.90MV/24HT)
Pole	Pol	Pole	Polo										