

# 'DINLET' - The unique DIN Rail Mount Dual Receptacle

**Snaps easily onto any TS35 symmetrical, 35 mm wide, DIN rail**



## Features

- Readily accessible power outlets
- Meets UL safety requirements for Canada and U.S.
- Integrated, clearly marked, screw clamp terminals
- Vertical mounting on any TS35 DIN rail
- Requires only 1.75" width of rail space
- Touch proof wire terminations for safety
- Low cost

Our high quality, fully enclosed, dual AC receptacle module offers two convenient 120Vac, 15A single-phase power outlets. DINlet operates on a 120V, single-phase AC source. Incoming Line, Neutral, and Ground lines connect to touch-proof screw clamp terminals, ensuring operator safety. These terminals accept 22 - 12 AWG solid or stranded conductors.

The DINlet can be quickly mounted vertically on any TS35 symmetrical DIN rail in control and equipment cabinets. Eliminate the need for extension cords to maintain and upgrade control cabinets; simply plug in test equipment, portable computers, soldering irons, lighting, and many other devices.

## Technical Specifications

Operating temperature	To 60°C
Terminal connection	22 -12 AWG solid or stranded copper wire
Flammability	UL V0
Material	Impact resistant thermoplastic
Color	Light grey
UL file #	E233903



To meet all your panel building and wire management needs, ICD also supplies:

- Enclosures, DIN Rails
  - Terminal Blocks, Wiring Duct, Wire Ferrules.
  - Fuse Holders, Power Supplies, Push Buttons, Selector Switches, Key Switches, LED Indicators.
  - Programmable Controller
  - Relays and Timers
  - Signal Conditioners
- and a lot more products!**

Visit us !

[www.IndustrialControlDirect.com](http://www.IndustrialControlDirect.com)

---

---

**Technical data**

**Electrical ratings**

Volts: 125  
Amps: 15 Amps Max.  
Wire range: 18-14 AWG  
Clamp torque: 3.5 - 5.3 lb. in. (0.4 - 0.6 Nm)

**DIN rail mounting compatibility**

Din 3 only

**Materials information reference**

Housing: 25% glass reinforced PA6/66 V0  
Connectors: Chromium Oxide plated steel  
Operating temperatures: -40°C MIN +70°C MAX  
Flammability specs: Halogen-free, UL rated 94 V0  
Ingress protection: IP20

**Configuration**

NEMA 5-15R

**Color**

Ivory

**Approvals**

UL

**Approximate dimensions – (mm [in])**

