



# Screwless Terminal Blocks (Push Fit)

	21.4200M	21.4201M	21.4200MF	21.5100M	21.5200M	21.5300M	21.5400M
Pitch	Höhe	Pas	Passo				
Technical data	Technische Daten	Documentation technique	Dati tecnici				
Rated voltage	Nennspannung	Tension assignée	Tensione nominale	300V	450V	300V	450V
Rated current	Nennstrom	Courant assigné	Corrente nominale	14A	12A	14A	12A
Wire range	Drahtbereich	Gamme des fils	Tipi di cavo	1.5mm <sup>2</sup>	2.5mm <sup>2</sup>	1.5mm <sup>2</sup>	2.5mm <sup>2</sup>
Solid wire (AWG)	Massivdraht (AWG)	Fil rigide (AWG)	Cavo rigido (AWG)	28-14	28-12	28-14	22-14
Stranded wire (AWG)	Normaldraht (AWG)	Fil standard (AWG)	Cavo standard (AWG)	28-12	28-12	26-20	22-14
Rated surge voltage (UL/IEC(max))	Bemessungsstossspannung (max)	Surintention nominale (max)	Sovratensione nominale (max)	1.6/2.5/4kV	1.6/2.5/4kV	1.3/1.25/2kV	1.3/1.25/2kV
Wire Strip length	Drahtabisolierlänge	Longueur isolée du fil	Lunghezza spellaggio cavo	8-9mm	8-9mm	9-10mm	9-10mm
Part no.	Artikelbez	Numéro d'identification	Part. No.				
Pole	Pol	Pôle	Polo	21.4200M/2 21.4200M/24	21.4201M/2 21.4201M/24	21.4200MF/2 21.4200MF/24	21.5100M/2 21.5100M/24

	21.5500M	21.5600M	21.4200M	21.4300M	20.4100M	20.4400M	21.4102M
Pitch	Höhe	Pas	Passo				
Technical data	Technische Daten	Documentation technique	Dati tecnici				
Rated voltage	Nennspannung	Tension assignée	Tensione nominale	300V	750V	300V	750V
Rated current	Nennstrom	Courant assigné	Corrente nominale	10A	12A	10A	12A
Wire range	Drahtbereich	Gamme des fils	Tipi di cavo	2.5mm <sup>2</sup>	2.5mm <sup>2</sup>	1.5mm <sup>2</sup>	2.5mm <sup>2</sup>
Solid wire (AWG)	Massivdraht (AWG)	Fil rigide (AWG)	Cavo rigido (AWG)	22-14	22-14	20-14	20-14
Stranded wire (AWG)	Normaldraht (AWG)	Fil standard (AWG)	Cavo standard (AWG)	22-14	22-14	20-14	20-14
Rated surge voltage (UL/IEC(max))	Bemessungsstossspannung (max)	Surintention nominale (max)	Sovratensione nominale (max)	1.6/3/4kV	1.6/3/4kV	1.6/2/4kV	1.6/2/4kV
Wire Strip length	Drahtabisolierlänge	Longueur isolée du fil	Lunghezza spellaggio cavo	6-7mm	6-7mm	6-7mm	6-7mm
End cover	Endabdeckung	Plaque d'extrémité	Copertura	21.4200EP	21.4300EP	20.4100EP	20.4400EP
Part no.	Artikelbez	Numéro d'identification	Part. No.				
Pole	Pol	Pôle	Polo	21.5500M/2 21.5500M/24	21.5600M/2 21.5600M/24	21.4200M/2 21.4200M/24	21.4300M/2 21.4300M/24

# Screwless Terminal Blocks (Push Fit)



Pitch	Höhe	Pas	Passo
Technical data	Technische Daten	Documentation technique	Dati tecnici
Rated voltage	Nennspannung	Tension assignée	Tensione nominale
Rated current	Nennstrom	Courant assigné	Corrente nominale
Wire range	Drahtbereich	Gamme des fils	Tipi di cavo
Solid wire (AWG)	Massivdraht (AWG)	Fil rigide (AWG)	Cavo rigido (AWG)
Stranded wire (AWG)	Normaldraht (AWG)	Fil standard (AWG)	Cavo standard (AWG)
Rated surge voltage (UL/IEC(max))	Bemessungsstossspannung (max)	Surintention nominale (max)	Sovratensione nominale (max)
Wire Strip length	Drahtabisolierlänge	Longueur isolée du fil	Lunghezza spellaggio cavo
End cover	Endabdeckung	Plaque d'extrémité	Copertura
Part no.	Artikelbez	Numéro d'identification	Part. No.
Pole	Pol	Pôle	Polo

	21.4103M	20.4101M	21.4104M	20.4500M	20.4105M
	3.96mm	5.00mm	7.50mm	5.00mm	7.50mm
	UL IEC	UL IEC	UL IEC	UL IEC	UL IEC
Rated voltage	300V 250V	300V 450V	300V 450V	300V 450V	300V 750V
Rated current	10A 17.5A	10A 24A	10A 24A	10A 12A	10A 12A
Wire range	1.5mm <sup>2</sup>	2.5mm <sup>2</sup>	2.5mm <sup>2</sup>	0.75mm <sup>2</sup>	0.75mm <sup>2</sup>
Solid wire (AWG)	20-14	20-14	20-14	24-18	24-18
Stranded wire (AWG)	20-14	20-14	20-14	24-18	24-18
Rated surge voltage (UL/IEC(max))	1.6/2.5/4kV	1.6/2.5/4kV	1.6/2.5/4kV	1.6/3/3kV	1.6/3/3kV
Wire Strip length	6-7mm	6-7mm	6-7mm	9-10mm	9-10mm
End cover	21.4103EP	20.4101EP	21.4104EP	21.4500EP	21.4105EP
Part no.					
Pole	21.4103M/2 21.4103M/24	20.4101M/2 20.4101M/24	21.4104M/2 21.4104M/24	20.4500M/2 20.4500M/24	20.4105M/2 20.4105M/24