

Distribution Enclosure

- High thermal stability - ASA plastic
- Transparent door
- UV Stable
- Current rating 63A
- IP65 rating – Inside / Outside use
- Earth & neutral bars included
- Suitable for Photovoltaic applications
- Key accessory



Each enclosure comes with a set of accessories:

- 6 way divisible blanking plates
- 4x Wall plug and screws
- 4x internal screw caps
- Application identifier stickers

Options & Ordering Codes

E	—	04	W
Modules / Poles		04	
Modules / Poles		08	
Modules / Poles		12	
Modules / Poles		24	
Modules / Poles		36	

Technical Data

Protection Class	IP65
Isolation Class	II <input type="checkbox"/>
Impact Kit	IK07
Normal Voltage	400V AC / 1000V DC
Temperature Range	-25°C to +60°C
Colour	RAL 7035
IEC Capability	60670-24

Type	Description	No. of Terminals PE/N	Dimensions - mm (h x w x d)	Entries Description
E-04W	4 Module Enclosure	4/4	200 x 127 x 120	4 x M20 + 4x M25/M32
E-08W	8 Module Enclosure	8/8	200 x 200 x 120	8 x M20 + 6x M25/M32
E-12W	12 Module Enclosure	10/10	258 x 318 x 142	12 x M20 + 10x M25/M32 + 4x M32/M40 + 2x Knockout plate 37x90mm
E-24W	24 Module Enclosure	13/13	383 x 318 x 142	12 x M20 + 10x M25/M32 + 4x M32/M40 + 4x Knockout plate 37x90mm
E-36W	36 Module Enclosure	15/15	507 x 318 x 142	12 x M20 + 10x M25/M32 + 4x M32/M40 + 6x Knockout plate 37x90mm